

# SAFETY DATA SHEET

SEE DESIGN

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name SEE DESIGN

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant for chains, wires and cables.

### 1.3. Details of the supplier of the safety data sheet

Supplier **STARBRITE CHEMICALS LTD**  
UNIT 27, BOLNEY GRANGE BUSINESS PARK  
STAIRBRIDGE LANE  
BOLNEY  
W SUSSEX  
RH17 5PB  
UNITED KINGDOM  
  
Tel. 01444 237 700  
Fax. 01444 237 701  
email warehouse@starbrite.co.uk

### 1.4. Emergency telephone number

National emergency telephone number Mon to Fri 8.30am to 5.00pm - 01444 237 700

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification

##### Physical hazards

Aerosol 1 - H222, H229

##### Health hazards

Not Classified

##### Environmental hazards

Not Classified

Classification (67/548/EEC or 1999/45/EC)

F+;R12.

### 2.2. Label elements

#### Pictogram



Signal word Danger

#### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated

#### Precautionary statements

## SEE DESIGN

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

### **2.3. Other hazards**

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

## **SECTION 3: Composition/information on ingredients**

### **3.2. Mixtures**

|   |  |
|---|--|
| <b>BUTANE</b>   | <b>30-60%</b>  |
| <b>CAS number:</b> 106-97-8 <b>EC number:</b> 203-448-7                     |  |
| <b>Classification</b><br>Flam. Gas 1 - H220<br>Press. Gas, Liquefied - H280 | <b>Classification (67/548/EEC or 1999/45/EC)</b><br>F+;R12 |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

#### **General information**

Treat symptomatically.

#### **Inhalation**

Move affected person to fresh air at once. Keep affected person warm and at rest. For breathing difficulties oxygen may be necessary. Get medical attention immediately.

#### **Ingestion**

Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention.

#### **Skin contact**

Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

#### **Eye contact**

Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### **4.2. Most important symptoms and effects, both acute and delayed**

#### **General information**

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

#### **Inhalation**

Vapours in high concentrations are anaesthetic. Central nervous system depression. Fatigue. Headache. Dizziness. Symptoms following overexposure may include the following:

#### **Ingestion**

Causes chemical burns to mouth, throat and stomach. May cause stomach pain or vomiting.

#### **Skin contact**

No specific symptoms known.

#### **Eye contact**

Irritation of eyes and mucous membranes.

### **4.3. Indication of any immediate medical attention and special treatment needed**

#### **Notes for the doctor**

SEE DESIGN

Treat symptomatically.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Extinguish with the following media: Dry chemicals, sand, dolomite etc. Powder. Water spray, fog or mist.

### **5.2. Special hazards arising from the substance or mixture**

#### **Specific hazards**

Containers can burst violently or explode when heated, due to excessive pressure build-up.

### **5.3. Advice for firefighters**

#### **Protective actions during firefighting**

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

#### **Special protective equipment for firefighters**

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **Personal precautions**

For personal protection, see Section 8.

### **6.2. Environmental precautions**

#### **Environmental precautions**

Any spillage needs to be contained and not allowed to enter water courses

### **6.3. Methods and material for containment and cleaning up**

#### **Methods for cleaning up**

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. If leakage cannot be stopped, evacuate area. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.

### **6.4. Reference to other sections**

#### **Reference to other sections**

For personal protection, see Section 8. For waste disposal, see Section 13.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Usage precautions**

Keep away from heat, sparks and open flame. Use approved respirator if air contamination is above an acceptable level. Avoid spilling. Provide adequate ventilation. Avoid inhalation of vapours. Avoid contact with skin and eyes.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Storage precautions**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### **7.3. Specific end use(s)**

#### **Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

#### **Usage description**

See product label for detailed usage and instructions.

## **SECTION 8: Exposure Controls/personal protection**

### **8.1. Control parameters**

SEE DESIGN

### Occupational exposure limits

#### **BUTANE**

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

#### **Ingredient comments**

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

#### **Protective equipment**



#### **Appropriate engineering controls**

Provide adequate general and local exhaust ventilation.

#### **Eye/face protection**

The following protection should be worn: Chemical splash goggles.

#### **Hand protection**

To protect hands from chemicals, gloves should comply with European Standard EN374.

#### **Other skin and body protection**

General workwear only

#### **Hygiene measures**

DO NOT SMOKE IN WORK AREA!

---

## **SECTION 9: Physical and Chemical Properties**

### 9.1. Information on basic physical and chemical properties

#### **Appearance**

Aerosol.

#### **Colour**

Dark brown.

#### **Odour**

Oil-like.

#### **pH**

pH (concentrated solution): Not applicable - non aqueous system

#### **Flash point**

- 74°C N/A.

#### **Upper/lower flammability or explosive limits**

: 1.8

#### **Relative density**

0.717 @ @ 20°C

#### **Solubility(ies)**

Insoluble in water

#### **Auto-ignition temperature**

+ 405°C

#### **Comments**

Information given relates to total aerosol container contents.

### 9.2. Other information

SEE DESIGN

#### Other information

None.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

May react with other cleaning chemicals. For specific reactions refer to Section 10.5

#### 10.2. Chemical stability

##### Stability

Stable at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Toxicological effects

No toxicological data is available for this mixture, however data can be provided for specific raw materials upon request.

##### Inhalation

Gas or vapour in high concentrations may irritate the respiratory system. Fatigue. Unconsciousness. Symptoms following overexposure may include the following: Headache. Nausea, vomiting. Gas or vapour displaces oxygen available for breathing (asphyxiant).

##### Ingestion

May cause burns in mucous membranes, throat, oesophagus and stomach. May cause stomach pain or vomiting.

##### Skin contact

No specific health hazards known.

##### Eye contact

Irritation of eyes and mucous membranes.

### SECTION 12: Ecological Information

#### Ecotoxicity

Not classed as Hazardous to the Environment but release to the environment should be avoided.

#### 12.1. Toxicity

Aquatic toxicity has not been carried out on this product. Data for raw materials contained in this product, when available, can be provided when necessary.

#### 12.2. Persistence and degradability

##### Persistence and degradability

The product is biodegradable.

#### 12.3. Bioaccumulative potential

The product does not contain any substances expected to be bioaccumulating.

#### 12.4. Mobility in soil

##### Mobility

The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

SEE DESIGN

#### **12.5. Results of PBT and vPvB assessment**

This product does not contain any substances classified as PBT or vPvB.

#### **12.6. Other adverse effects**

None known.

### **SECTION 13: Disposal considerations**

#### **13.1. Waste treatment methods**

##### **Disposal methods**

Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### **SECTION 14: Transport information**

#### **14.1. UN number**

|                  |      |
|------------------|------|
| UN No. (ADR/RID) | 1950 |
| UN No. (IMDG)    | 1950 |
| UN No. (ICAO)    | 1950 |

#### **14.2. UN proper shipping name**

|                                |                     |
|--------------------------------|---------------------|
| Proper shipping name (ADR/RID) | AEROSOLS, FLAMMABLE |
| Proper shipping name (IMDG)    | AEROSOLS, FLAMMABLE |
| Proper shipping name (ICAO)    | AEROSOLS, FLAMMABLE |
| Proper shipping name (ADN)     | AEROSOLS, FLAMMABLE |

#### **14.3. Transport hazard class(es)**

|                     |     |               |            |
|---------------------|-----|---------------|------------|
| ADR/RID class       | 2   | Class Code:5F | Label: 2.1 |
| IMDG class          | 2.1 |               |            |
| ICAO class/division | 2.1 |               |            |

#### **14.4. Packing group**

Not applicable.

|                    |     |
|--------------------|-----|
| IMDG packing group | N/A |
| ICAO packing group | N/A |

#### **14.5. Environmental hazards**

#### **14.6. Special precautions for user**

Tunnel restriction code (D)

#### **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

### **SECTION 15: Regulatory information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **National regulations**

Control of Substances Hazardous to Health Regulations 2002 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

##### **EU legislation**

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the

## SEE DESIGN

Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### Guidance

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. Approved Classification and Labelling Guide (Sixth edition) L131. CHIP for everyone HSG228.

### 15.2. Chemical safety assessment

No chemical assessment has been carried out as this Safety Data Sheet is for a mixture.

## SECTION 16: Other information

### General information

The following risk phrases relate to the raw materials in the product and not the product itself:-

### Revision comments

Safety Data Sheet revised to be in accordance with EU Regulation No 453/2010 - REACH Regulations.

**Revision date** 30/12/2014

**Revision** 9

### Risk phrases in full

R12 Extremely flammable.

### Hazard statements in full

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H280 Contains gas under pressure; may explode if heated.